





Compact PLC Series - Up to 320 I/Os	CPM2C	CP1E	CP1L	CP1H
				
<b>Maximum digital I/O points</b>	106 to 192	180	180	320
<b>Execution time. (bit instructions)</b>	0.26 to 0.64 $\mu$ s	1.19 $\mu$ s	0.55 $\mu$ s	0.1 $\mu$ s
<b>Program memory</b>	4K words	2 or 8K steps	10K steps	20K steps
<b>Data memory</b>	2K words	2 or 8K words	32K words	32K words
<b>Special functions</b>	20 kHz counter input, two 10 kHz pulse outputs	Six high speed inputs, two pulse outputs, up to two serial ports	Four 100 kHz counter inputs, two 100 kHz pulse outputs, two optional serial ports	CPUs with built-in pulse I/O and analog I/O. Expansion by CJ1 special I/O
<b>Communications</b>	Serial, DeviceNet, CompoBus/S, DeviceNet-to-CompoBus/S gateway function	Ethernet, Serial, DeviceNet, PROFIBUS-DP, CompoBus/S	Ethernet, Serial, DeviceNet, PROFIBUS-DP, CompoBus/S	Ethernet, Serial, Controller Link, DeviceNet, PROFIBUS-DP, CAN, CompoBus/S